



City Line



Production method	ISO 2424:	Tufted, 1/12" looppile
Primary backing	ISO 2424:	PA/PES nonwoven; colback
Secondary backing	ISO 2424:	Bitumen with glassfibers
Pile Composition	ISO 2076:	100% solution dyed polyamid
Number of knots /m ²	ISO 1763:	± 218,000
Pile height	ISO 1766:	± 1,9 mm.
Total thickness	ISO 1765:	± 5,8 mm.
Pile weight	ISO 2424:	± 550 gr./m ²
Total weight	ISO 8543	± 4150 gr./m ²
Pile density	ISO 8543:	± 0,188 gr./cm ³
Product Dimension	ISO 3018:	50X50 cm.
Tiles per Box		20 (5 m ²)
Colours		5
Wear Rating	EN 1307:	Class 33
Comfort class	EN 1307:	LC1
Castor chair	EN 985 / A:	Class 33
IBM/ICL test	EN 1963 / B:	Pass
Permanent antistatic		Yes
Walk on test	ISO 6356:	< 2 kV
Horizontal resistance	ISO 10965:	≤ 10 ⁹ Ω
Vertical resistance	ISO 10965:	≤ 10 ⁹ Ω
Impact noise reduction	ISO 140-8:	22 dB
Sound absorption	ISO 354:	Hz 0,2 α _s 0,2
Dimension stability	ISO 2551:	< 0,2%
Fire retardancy	ISO13501-01: BS 4790:	Bfl-S1 low radius of char
Thermal resistance	ISO 8302:	0,09 m ² .K/W
Light fastness	ISO 105 B02:	≥ 6
Waterfastness	ISO 105 E01:	5
Rubfastness	ISO 105 X12:	5
Factory guarantee		10 years



We reserve the right to amend the technical specifications.
Subject to slight color and structural deviations.

MARLIN CONTRACT BV, Marketing 3, NL 6921 RE Duiven, The Netherlands
Tel.: 0031 263121 639, Fax.: 003126 3121593, E-mail: sales@marlincontract.com